RC7702V6 - High-end orbital sander with low profile and 285W power - 2,5mm stroke

RODCRAFT



Benefits

- Lightweight but very powerful, finishing sander
- Very high operating comfort with excellent performance
- Innovative exhaust air system always blows the exhaust air away from the user
- Pleasant housing shape for long, fatigue-free working sanding applications
- For finishing, matting and paint repair

Features

- High-end orbital sander with low profile and 285W power
- Single hand orbital sander with ergonomic grip
- Small stroke - 2,5mm
- Innovative swivel for exhaust to allow left and right hand work
- Only 107 mm high
- Insulating thermo rubber against cold and for good grip
- Motor speed can be easily adjusted with the operating hand during the sanding process
- Equipped with 150 mm velcro pad with 15 holes
- Delivered with two interchangeable suction ports with diameters 27 mm and 29 mm

Technical description		
Model	RC7702V6	
Part number	8951000021	
Length	205 mm	
Net weight	0.825 kg	
Average air consumption	7.5 l/s	
Average air consumption	450 l/mn	
Actual air consumption	9.2 l/s	
Actual air consumption	550 l/mn	
Min. hose size	8 mm	
Sound pressure	79.5 db(A)	
Sound Power	90.5 db(A)	
Vibration ISO	ISO-28927-3	
Vibration	3.8 m/s²	
Vibration uncertainty (K)	1.5 m/s²	
Pad diameter	150 mm - 5/16"	*6*

Pad type Hook & Loop	All products	
Paper size	150 mm	*6″*
Orbit diameter	2.5 mm	
Free speed	10000 rpm	
Pad holes number	15	
Spindle thread	5/16"-24UNF IG	
Central vacuum	All products	
Box dimensions	160x170x190	