



CP6910-P24 - Powerful, Durable & Comfortable



Benefits

- ▶ Ideal for a variety of heavy Industrial Maintenance applications
- ▶ Reliable & powerful oil bath Pinless Rocking Dog clutch
- ▶ Operator comfort with many ergonomic features
- ▶ 3-part construction reducing downtime maintenance

Features

- ▶ 1" Industrial Pistol impact wrench
- ▶ Oil Bath Pinless rocking dog clutch
- ▶ Durable Aluminum body & Rubber protective cover on clutch housing
- ▶ D-type side handle with Rubber grip
- ▶ Dual (hole & ring) type socket retainer
- ▶ Removable hole plate for suspension
- ▶ Metal trigger & reverse knob for longer durability
- ▶ 3-positions regulator & easy reverse

Technical description		
Model	CP6910-P24	
Part number	6151590070	
Length	290 mm	11.4"
Net weight	10.2 kg	22.5 lb
Side to center	55 mm	2.2"
Actual air consumption	19 l/s	40.2 cfm
Min. hose size	13 mm	1/2"
Sound pressure	97 db(A)	
Sound Power	108 db(A)	
Vibration ISO	ISO-28927-2	
Vibration	8.9 m/s ²	
Vibration uncertainty (K)	2.5 m/s ²	
Handle type	Pistol	
Square drive	1"	

Working Torque Range (fwd)	500 - 2,100 Nm	370 - 1,550
Maximum Torque (reverse)	2600 Nm	1920 ft.lbs
Free speed	5000 rpm	
Blows per minute	650	
Power/weight ratio	254.9 Nm/kg	85.3 ft.lb/lb
VST2	37.7	
Socket retainer	Dual (hole+friction)	
Clutch type	Pinless Rocking Dog - Oil bath	
European Standards	EN ISO 11148-6:2013	