Chicago Pneumatic

CP7215 - Powerful & comfortable



Benefits

- Operator comfort with ergonomic palm shape
- Productivity increased with low vibrations level
- Powerful and ergonomic palm shape for vertical and horizontal applications
- 3/8" (10 mm): great for heavy material removal such as body filler

Features

- 6" (150 mm) random orbital palm sander
- 3/8" (10 mm) orbit
- Powerful 0.29 hp (210 W) motor
- Soft grip, tear drop design for perfect control
- Low noise level
- Shut-off and speed control switch
- Non Vacuum (NV) model in PSA pad

Technical description		
Model	CP7215	
Part number	8941072151	
Length	185 mm	6.3"
Net weight	0.79 kg	1.74 lb
Height	105 mm	4.1"
Width	150 mm	6"
Average air consumption	3.8 l/s	8 cfm
Average air consumption	227 l/mn	8 cfm
Actual air consumption	7.6 l/s	16 cfm
Actual air consumption	453 l/mn	16 cfm
Free speed air consumption	8 l/s	18 cfm
Min. hose size	10 mm	3/8"
Sound pressure	81 db(A)	

Sound Power	92 db(A)	
European Sound standard	EN ISO 15744	
Vibration ISO	ISO-28927-3	
Vibration	8.54 m/s²	
Vibration uncertainty (K)	2.85 m/s²	
Pad diameter	150 mm	*6"*
Pad type Hook & Loop	no	
Pad type PSA	yes	
Pad type	PSA	
Paper size	150 mm	*6"*
Orbit diameter	10 mm	*3/8"*
Free speed	12000 rpm	
Power	210 W	*0.3 hp*
Vacuum	no	
Pad holes number	0	
Height over spindle	105 mm	*4.1"*
Spindle thread	5/16-24	
No-vacuum	No-vacuum	
European Directives	2006/42/EC (17/05/2006)	
European Standards	EN ISO 11148-8 : 2012	