



for International Market (excluding UK)



Type PKT range of end sleeves is manufactured from Tin plated electrolytic Copper. The PA6 insulation type PA10080 is certified EN45545-2. Designed to accommodate two cables terminating in the same sleeve. The operating temperature range is -20 to +120°C (Surge +130°C).

Recommended crimping tools are shown on pages 188 to 228, 279-281, 312, 314, 316-319.

Conductor Size sqmm	Type	Dimensions mm				Insulation Colour	ND1,ND2,ND3, ND4 and HNKE 50 Compression Aperture	Quantity Box/Bag
		C	B	P	L			
2 x 0,5	PKT508	4,7x2,5	1,80	8,0	15,0	white	1	5.000/500
	PKT510*	4,7x2,5	1,80	10,0	18,0			5.000/500
2 x 0,75	PKT7508	5,0x2,8	2,10	8,0	15,0	grey	1,5	2.500/100
	PKT7510	5,0x2,8	2,10	10,0	17,0			2.500/100
2 x 1	PKT108	5,4x3,4	2,35	8,0	15,0	red	2,5	2.500/100
	PKT110	5,4x3,4	2,35	10,0	17,0			2.500/100
2 x 1,5	PKT1508	6,6x3,6	2,50	8,0	16,0	black	2,5	2.500/100
	PKT1512	6,6x3,6	2,50	12,0	20,0			2.500/100
2 x 2,5	PKT2510	7,8x4,2	3,20	10,0	18,5	blue	4	2.000/100
	PKT2512	7,8x4,2	3,20	13,0	21,5			1.500/100
2 x 4	PKT412	8,8x4,9	4,10	12,0	23,0	grey	6	1.000/100
2 x 6	PKT614	10,0x6,9	5,20	14,0	26,0	yellow	10	800/100
2 x 10	PKT1014*	13,0x7,2	6,70	14,0	26,0	red	16	500/50
2 x 16	PKT1614	18,4x9,6	8,90	14,0	30,0	blue	35	200/50

*Not UL approved